

AQUASOL RETARDER

Advance water-based lacquer reducer

April 2018

PRODUCT INTRODUCTION

Description	Retarder for Aquasol products.
Uses	Use in combination with Aquasol products for application on furniture, flooring and paneling made from timber.
Application	Mix required amount into Woodflex product and stir to homogeneity.

PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity at 27 (°C)	1.00 – 1.06
Solid Content (%)	Not applicable
Viscosity (at 27 °C)	9 – 12 sec F#4 Cup

PRODUCT PREPARATION

Mixing Ratio	Aquasol product. 100 parts by weight
	Aquasol Retarder 0 to 3 parts by weight

APPLICATION PARAMETER

Theoretical Coverage	Variable, depending on specific Aquasol product.
Coating System	Variable, depending on specific Aquasol coating system.

GENERAL PROPERTIES

Aquasol Retarder is a water-based retarder formulated specially to enhance the workability of Aquasol products on timber substrate.

SHELF LIFE

12 months from date of manufacture. The date refers to product held in its original closed packaging.

STORAGE

Keep containers in a cool ventilated environment, temperature between 5 °C to 40 °C. With partial use, close container tight and use the remainder as soon as possible.